

Specifications SMART Board® MX075-V2 Pro interactive display with iQ

Model SBID-MX275-V2-PW

Overview


The SMART Board[®] MX275-V2 Pro interactive display with iQ is great value for businesses that need an interactive display on a budget. The 75" 4K Ultra HD resolution display includes a license to SMART Meeting Pro[®] and a standard three-year warranty.

The iQ experience offers one-touch access to collaboration tools, including a digital whiteboard, a web browser, and wireless screen sharing.



Dimensions and weights¹

Dimensions



Weight

142 lb. (64.3 kg) Active touch area 66 1/2" × 38" (168.8 cm × 96.6 cm) Active image area 65" × 36 1/2" × (165 cm × 92.8 cm) Shipping dimensions (including pallet) 75" W × 50 1/4" H × 11 5/8" D (190.5 cm × 127.7 cm × 29.5 cm) Shipping weight 192 lb. (87 kg)



As an ENERGY STAR[®] certified signage display, the SMART Board MX075-V2 interactive display meets strict energy efficiency guidelines set by the U.S. Environmental Protection Agency and Department of Energy.

¹All dimensions \pm 1/8" (0.3 cm). All weights \pm 2 lb. (0.9 kg).

Hardware

Interaction

Touch technology	HyPr Touch [™] with Advanced IR
Multitouch capabilities	Up to 20 simultaneous touch, writing, or erase points ^{2 3}
Object Awareness™	Behavior adjusts automatically to the tool or object you're using, whether it's a pen, finger or palm.
Positioning accuracy	<2 mm
Display	
Туре	LED backlit LCD (A grade)
Aspect ratio	16:9
Resolution	4K UHD (3840 × 2160)
Horizontal frequency	31 Hz–140 kHz
Vertical frequency	59 Hz–70 Hz
Brightness (maximum)	≥400 cd/m ²
Refresh frequency	60 Hz
Pixel clock (maximum)	600 MHz
Pixel dimensions	0.43 mm
Viewing angle	178°
Response time (typical)	8 ms
Ambient light sensor	Yes
Bluetooth®	Bluetooth 4.2 dual mode (backwards compatible with Bluetooth 2.1 + EDR)
Audio	15 W integrated speakers (×2)
Wireless	IEEE 802.11a/b/g/n/ac with 2 × 2 MIMO (both 2.4 and 5 GHz bands)
Included cables and accessories	Country-specific power cable 16' 5" (5 m) USB cable Wall mount bracket kit Pen (×2) Antenna (×2) IR remote control (with two AAA batteries)
Mounting holes	For a standard VESA® 600 mm × 400 mm mounting plate with M8 screws
Mounting bracket depth	Minimum clearance depth of 11/4" (3 cm) for all components on the back of the interactive display for airflow

²Requires the latest version of SMART Product Drivers to be installed. Some applications might not support all touch points.

³Chrome OS is limited to 10 simultaneous touches. Pens and eraser are not supported.

iQ experience

iQ experience	iQ experience embedded in the display provides better performance without the need to install a separate appliance
Included apps and features	Customizable Home screen Whiteboard Browser Screen Share File and app libraries Writing and drawing over any input Freeze screen and screen shade Automatic software updates
Supported languages	Chinese (simplified) Chinese (traditional) Danish Dutch English Finnish French German Italian Korean Norwegian Portuguese Russian Spanish Swedish Ukrainian

Software

Included	iQ Android-based embedded computing
software	SMART Ink and SMART Product Drivers
	Subscription to SMART TeamWorks Room edition (included with the SMART Pro service plan for the
	service plan's term)
	One SMART Meeting Pro software room license (included with SMART Pro service plan)
	Subscription to SMART Remote Management for the length of warranty

SPECIFICATIONS SMART BOARD MX075-V2 PRO INTERACTIVE DISPLAY WITH IQ – MODEL SBID-MX275-V2-PW

Connectors

Cido connector nonal	
Side connector panel	1 Accessory slot (for 60W OPS devices)
	1 HDMI [®] 2.0 out with HDCP 2.2 support ⁴
	1 USB 2.0 Type-A (for service use only)
	1 USB 3.0 Type-A (for currently selected input source)
	HDMI 1
	1 HDMI 2.0 in with HDCP 1.4 and HDCP 2.2 support
	1 USB 3.0 Type-B (for touch)
	HDMI 2
	1 HDMI 2.0 with HDCP 1.4 and HDCP 2.2 support
	1 USB 3.0 Type-B (for touch)
Front connector panel	1 USB 2.0 Type-A (for the display)
	1 USB 2.0 Type-A (for currently selected input source)
	HDMI 3
	1 HDMI 2.0 in with HDCP 1.4 and HDCP 2.2 support
	1 USB 2.0 Type-B (for touch)
Bottom connector	1 RS-232
panel	2 RJ45
	1 S/PDIF out (fixed)
	1 Stereo 3.5 mm out (variable)
	VGA 1
	1 Stereo 3.5 mm in (for VGA in)
	1 VGA in
	1 USB 3.0 Type-B (for touch)

Installation requirements

Interactive display See the SMART Board MX (V2) and MX (V2) Pro series interactive displays installation and maintenance guide (smarttech.com/kb/171555)

IMPORTANT

The display needs an internet connection for downloading and installing important updates. Ask the network administrator to configure the network correctly for the iQ experience. For more information about network configuration, see Connecting a SMART display with the iQ experience to a network.

Room computers and guest laptops

General requirements	See SMART TeamWorks software release notes or SMART Meeting Pro software release notes
4K UHD	Video card that can support 3840 × 2160 resolution at 60 Hz
	See Minimum requirements for Ultra High Definition or 4K on your interactive flat panel

⁴HDCP is always enabled. Content is shown in 480p resolution if the external display doesn't support HDCP.

Cable requirements

HDMI	Maximum length: 23' (7 m)
	NOTES
	 Use only certified HDMI cables that have been tested to support the performance standard you require.
	• The performance of cables longer than 23' (7 m) is highly dependent on the cable's quality.
USB 2.0	USB 2.0 certified Hi-Speed (480 Mbps) support Maximum length: 16' (5 m)
USB 3.0	USB 3.0 certified SuperSpeed (5 Gbps) support Maximum length: 9' (3 m)
	NOTES
	 SMART supports only installations that use directly connected video and USB cables, AC-powered extenders, or USB extenders purchased from SMART.
	• You might be able to use higher-grade cables that are longer than specified. If you have problems with such a cable or an extender of any type, test the connection with a shorter cable before contacting SMART Support.
Important	Using cables that exceed these maximum lengths can produce unexpected results, such as degraded picture quality or USB connectivity. Refer to <i>Installation best practices for SMART products</i> (smarttech.com/kb/171035) for comprehensive information about cables and extensions for SMART hardware products.
Storage and operati	ng requirements
Power requirements	100V to 240V AC, 50 Hz to 60 Hz
Standalone interactive di	splay power consumption at 77°F (25°C)
Standby mode	≤0.5 W
Normal operating (out-of-box)	114 W
Operating temperature	41–95°F (5–35°C)
Storage temperature	-4–140°F (-20–60°C)

Humidity 5–80% relative humidity, non-condensing

Certification and compliance (Model ID: IDX75-2)

U.S. / Canada FCC, ISED, UL, CONEG Packaging, Cal Prop 65, Conflict Minerals, Energy Star

SPECIFICATIONS SMART BOARD MX075-V2 PRO INTERACTIVE DISPLAY WITH IQ – MODEL SBID-MX275-V2-PW

EU / EEA / EFTA	CE - LVD, RED, REACH, RoHS, Battery, WEEE, Packaging
EAEU	EAC
Australia / New Zealand	RCM
Taiwan	BSMI, NCC
Vietnam	ICT
Purchasing informati Order number SBID-MX275-V2-PW	ON SMART Board MX075-V2 Pro interactive display with iQ – White
Optional accessories	
Other	See smarttech.com/accessories
Warranty information	

SMART Assure warranty Includes advanced hardware replacement and access to onsite support. Terms and conditions vary by region. Contact your local reseller or distributor for information and visit smarttech.com/warranty.

smarttech.com/support smarttech.com/contactsupport

© 2020 SMART Technologies ULC. All rights reserved. SMART Board, SMART Meeting Pro, Pen ID, HyPr Touch, Object Awareness, Silktouch, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. The Bluetooth word mark is owned by the Bluetooth SIG, Inc. and any use of such marks by SMART Technologies ULC is under license. The Adopted Trademarks HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. All other third-party product and company names may be trademarks of their respective owners. This product and/or use thereof is covered by one or more of the following U.S. patents: www.smarttech.com/patents. Contents are subject to change without notice. April 3, 2020.